

Section 1. Identification

Product identifier : SERIOLA QA 46

Recommended use of the chemical and restrictions on use

Not applicable.

Supplier's details : TotalEnergies Lubrifiants
562 Avenue du Parc de L'île
92029 Nanterre Cedex FRANCE
Tél: +33 (0)1 41 35 40 00
Fax: +33 (0)1 41 35 84 71
rm.msds-lubs@totalenergies.com

TotalEnergies Marketing Asia-Pacific Middle East Pte. Ltd.
182 Cecil Street
#27-01 Frasers Tower
Singapore 069547
Tel: +65 6879 2200
ms.ap-sds@totalenergies.com
See section 16 to have the contact details of the local supplier

Emergency telephone number :

Asia-Pacific: +65 3158 1074
Middle-East: +44 1235 239671

Section 2. Hazard identification

Classification of the substance or mixture : Not classified.

GHS label elements

Signal word : No signal word.
Hazard statements : No known significant effects or critical hazards.

Precautionary statements

Prevention : Not applicable.
Response : Not applicable.
Storage : Not applicable.
Disposal : Not applicable.

Other hazards which do not result in classification : None known.

Section 3. Composition/information on ingredients

Substance/mixture : Mixture

Ingredient name	% (w/w)	Identifiers
Distillates (petroleum), hydrotreated heavy paraffinic	≥25 - ≤50	64742-54-7
Paraffin oils (petroleum), catalytic dewaxed heavy	≥10 - ≤25	64742-70-7

There are no ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

- Eye contact** : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Get medical attention if irritation occurs.
- Inhalation** : Remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical attention if symptoms occur.
- Skin contact** : Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Get medical attention if symptoms occur.
- Ingestion** : Wash out mouth with water. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Do not induce vomiting unless directed to do so by medical personnel. Get medical attention if symptoms occur.

Most important symptoms/effects, acute and delayed

Potential acute health effects

- Eye contact** : No known significant effects or critical hazards.
- Inhalation** : No known significant effects or critical hazards.
- Skin contact** : No known significant effects or critical hazards.
- Ingestion** : No known significant effects or critical hazards.

Over-exposure signs/symptoms

- Eye contact** : No specific data.
- Inhalation** : No specific data.
- Skin contact** : No specific data.
- Ingestion** : No specific data.

Indication of immediate medical attention and special treatment needed, if necessary

- Notes to physician** : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
- Specific treatments** : No specific treatment.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media : Use dry chemical, CO₂, water spray (fog) or foam.

Unsuitable extinguishing media : Do not use water jet.

Specific hazards arising from the chemical : In a fire or if heated, a pressure increase will occur and the container may burst.

Hazardous thermal decomposition products : Carbon dioxide.
carbon monoxide
nitrogen oxides (NO, NO₂ etc.)

Special protective actions for fire-fighters : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

Special protective equipment for fire-fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Put on appropriate personal protective equipment.

For emergency responders : If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

Environmental precautions : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods and materials for containment and cleaning up

Small spill : Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill : Stop leak if without risk. Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

- Protective measures** : Put on appropriate personal protective equipment (see Section 8).
- Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

- Conditions for safe storage, including any incompatibilities** : Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits UN

Product/substance	Exposure limit values
Distillates (petroleum), hydrotreated heavy paraffinic	ACGIH TLV (United States, 1/2021). [Mineral Oil, pure, highly and severely refined] TWA: 5 mg/m ³ 8 hours. Form: Inhalable fraction
Paraffin oils (petroleum), catalytic dewaxed heavy	ACGIH TLV (United States, 1/2021). [Mineral Oil, pure, highly and severely refined] TWA: 5 mg/m ³ 8 hours. Form: Inhalable fraction

Occupational exposure limits Hong Kong

Product/substance	Exposure limit values
Distillates (petroleum), hydrotreated heavy paraffinic	Labour Department, OS&H Branch (Hong Kong, 4/2002). [Oil mist, mineral] STEL: 10 mg/m ³ 15 minutes. TWA: 5 mg/m ³ 8 hours.
Paraffin oils (petroleum), catalytic dewaxed heavy	Labour Department, OS&H Branch (Hong Kong, 4/2002). [Oil mist, mineral] STEL: 10 mg/m ³ 15 minutes. TWA: 5 mg/m ³ 8 hours.
Distillates (petroleum), hydrotreated heavy paraffinic	Labour Department, OS&H Branch (Hong Kong, 4/2002). [Oil mist, mineral] STEL: 10 mg/m ³ 15 minutes. TWA: 5 mg/m ³ 8 hours.
Distillates (petroleum), solvent-dewaxed heavy paraffinic	Labour Department, OS&H Branch (Hong Kong, 4/2002). [Oil mist, mineral] STEL: 10 mg/m ³ 15 minutes. TWA: 5 mg/m ³ 8 hours.

Occupational exposure limits India



Product/substance	Exposure limit values
Distillates (petroleum), hydrotreated heavy paraffinic	ACGIH TLV (United States, 1/2021). [Mineral Oil, pure, highly and severely refined] TWA: 5 mg/m ³ 8 hours. Form: Inhalable fraction
Paraffin oils (petroleum), catalytic dewaxed heavy	ACGIH TLV (United States, 1/2021). [Mineral Oil, pure, highly and severely refined] TWA: 5 mg/m ³ 8 hours. Form: Inhalable fraction
Distillates (petroleum), hydrotreated heavy paraffinic	ACGIH TLV (United States, 1/2021). [Mineral Oil, pure, highly and severely refined] TWA: 5 mg/m ³ 8 hours. Form: Inhalable fraction
Distillates (petroleum), solvent-dewaxed heavy paraffinic	ACGIH TLV (United States, 1/2021). [Mineral Oil, pure, highly and severely refined] TWA: 5 mg/m ³ 8 hours. Form: Inhalable fraction

- Appropriate engineering controls** : Good general ventilation should be sufficient to control worker exposure to airborne contaminants.
- Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
- Advisory OEL** : No known significant effects or critical hazards.

Individual protection measures

- Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
- Eye/face protection** : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.
- Skin protection**
- Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.
Hydrocarbon-proof gloves
Fluorinated rubber
nitrile rubber
Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time.
- Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Respiratory protection** : None under normal use conditions. If these are not sufficient to maintain exposure to dusts below the OEL, suitable respiratory protection must be worn. (Type A/P1)



Section 9. Physical and chemical properties and safety characteristics

The conditions of measurement of all properties are at standard temperature (20°C / 68°F) and pressure (1013 hPa) unless otherwise indicated

Appearance

Physical state	: Liquid.
Color	: Yellow.
Odor	: Characteristic.
Odor threshold	: Not available.
pH	: Not available.
Melting point/freezing point	: Not available.
Boiling point	: Not available.
Flash point	: Open cup: 247°C (476.6°F) [ASTM D 92]
Evaporation rate	: Not available.
Flammability (solid, gas)	: Not available.
Lower and upper explosive (flammable) limits	: Not available.
Vapor pressure	: Not available.
Vapor density	: Not available.
Relative density	: 0.879 [ASTM D 4052]
Density	: 0.879 g/cm ³ [15°C] [ASTM D 4052]
Solubility(ies)	:

Media	Result
cold water	Not soluble
hot water	Not soluble

Miscible with water : No.

Partition coefficient: n-octanol/water : Not applicable.

Auto-ignition temperature : Not available.

Decomposition temperature : Not available.

Viscosity : Kinematic (40°C (104°F)): 46.4 mm²/s (46.4 cSt) [ASTM D 445]

Flow time (ISO 2431) : Not available.

Particle characteristics

Median particle size : Not applicable.

Section 10. Stability and reactivity

Reactivity : No specific test data related to reactivity available for this product or its ingredients.

Chemical stability : Stable under recommended storage and handling conditions (see Section 7).

Possibility of hazardous reactions : Under normal conditions of storage and use, hazardous reactions will not occur.

Conditions to avoid : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Incompatible materials : Strong oxidizing agents

Hazardous decomposition products : Carbon dioxide.
carbon monoxide
nitrogen oxides (NO, NO₂ etc.)

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/substance	Result	Species	Dose	Exposure	Test
Distillates (petroleum), hydrotreated heavy paraffinic	LC50 Inhalation Dusts and mists	Rat - Male, Female	>5 mg/l	4 hours	OECD 403
	LD50 Dermal	Rabbit - Male, Female	>5000 mg/kg	-	Read across OECD 402
	LD50 Oral	Rat - Male, Female	>5000 mg/kg	-	Read across OECD 401
Paraffin oils (petroleum), catalytic dewaxed heavy	LC50 Inhalation Dusts and mists	Rat	5.1 mg/l	4 hours	-
	LC50 Inhalation Vapor	Rat	80.4 mg/l	1 hours	-
	LC50 Inhalation Vapor	Rat	20.1 mg/l	4 hours	-
	LD50 Dermal	Rabbit	>5000 mg/kg	-	-
	LD50 Oral	Rat	>5000 mg/kg	-	-

Conclusion/Summary : Based on available data, the classification criteria are not met.

Irritation/Corrosion

Skin : Based on available data, the classification criteria are not met.

Eyes : Based on available data, the classification criteria are not met.

Respiratory : Based on available data, the classification criteria are not met.

Sensitization

Skin : Based on available data, the classification criteria are not met.

Respiratory : Based on available data, the classification criteria are not met.

Mutagenicity

Conclusion/Summary : Based on available data, the classification criteria are not met.

Carcinogenicity

Conclusion/Summary : Based on available data, the classification criteria are not met.

Reproductive toxicity

Conclusion/Summary : Based on available data, the classification criteria are not met.

Teratogenicity

Conclusion/Summary : Based on available data, the classification criteria are not met.

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard



Name	Result
Distillates (petroleum), hydrotreated heavy paraffinic Paraffin oils (petroleum), catalytic dewaxed heavy	ASPIRATION HAZARD - Category 1 ASPIRATION HAZARD - Category 1

Conclusion/Summary : Based on available data, the classification criteria are not met.

Information on the likely routes of exposure : Not available.

Potential acute health effects

Eye contact : No known significant effects or critical hazards.
Inhalation : No known significant effects or critical hazards.
Skin contact : No known significant effects or critical hazards.
Ingestion : No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact : No specific data.
Inhalation : No specific data.
Skin contact : No specific data.
Ingestion : No specific data.

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

Potential immediate effects : Not available.
Potential delayed effects : Not available.

Long term exposure

Potential immediate effects : Not available.
Potential delayed effects : Not available.

Potential chronic health effects

Not available.

General : No known significant effects or critical hazards.
Carcinogenicity : No known significant effects or critical hazards.
Mutagenicity : No known significant effects or critical hazards.
Reproductive toxicity : No known significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates

Product/substance	Oral (mg/kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapors) (mg/l)	Inhalation (dusts and mists) (mg/l)
Paraffin oils (petroleum), catalytic dewaxed heavy	N/A	N/A	N/A	20.1	5.1

Section 12. Ecological information

Toxicity

Product/substance	Result	Species	Exposure	Test
Distillates (petroleum), hydrotreated heavy paraffinic	Acute EC50 >100 mg/l	Algae - Pseudokirchneriella subcapitata	72 hours	OECD 201
	Acute EC50 >10000 mg/l	Crustaceans - Daphnia magna	48 hours	OECD 202
	Chronic NOEL >100 mg/l	Algae - Pseudokirchneriella subcapitata	72 hours	OECD 201
	Chronic NOEL >1000 mg/l	Crustaceans - Daphnia magna	21 days	-
Paraffin oils (petroleum), catalytic dewaxed heavy	Acute EC50 10000 mg/l	Daphnia	48 hours	-
	Acute NOEL 101 mg/l	Algae - Pseudokirchneriella subcapitata	72 hours	-

Persistence and degradability

Product/substance	Test	Result	Dose	Inoculum
Distillates (petroleum), hydrotreated heavy paraffinic	OECD 301F	31 % - Not readily - 28 days	-	Activated sludge

Product/substance	Aquatic half-life	Photolysis	Biodegradability
Distillates (petroleum), hydrotreated heavy paraffinic	-	-	Not readily
Paraffin oils (petroleum), catalytic dewaxed heavy	-	-	Not readily

Bioaccumulative potential

Product/substance	LogK _{ow}	BCF	Potential
Distillates (petroleum), hydrotreated heavy paraffinic	>4	-	high

Mobility in soil

Soil/water partition coefficient (K_{oc})

: Not available.

Mobility in soil

: Given its physical and chemical characteristics, the product generally shows low soil mobility The product is insoluble and floats on water Loss by evaporation is limited

Other adverse effects

: No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

	ADR	IMDG	ICAO/IATA
UN/ID No	Not regulated.	Not regulated.	Not regulated.
UN proper shipping name	-	-	-
Transport hazard class(es)	-	-	-
Packing group	-	-	-
Environmental hazards	No.	No.	No.

Additional information

ADR : -

ICAO/IATA

Special precautions for user : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according to IMO instruments : Not available.

Section 15. Regulatory information

International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

Inventory list

Australia inventory (AIIC)	: Not determined.
Canada inventory (DSL/NDL)	: Not determined.
China inventory (IECSC)	: Not determined.
Europe inventory (EC)	: All components are listed or exempted.
Japan inventory	: Japan inventory (CSCL) : Not determined. Japan inventory (ISHL) : Not determined.
New Zealand Inventory of Chemicals (NZIoC)	: Not determined.
Philippines inventory (PICCS)	: Not determined.
Korea inventory (KECI)	: Not determined.
Taiwan Chemical Substances Inventory (TCSI)	: Not determined.
Thailand inventory	: Not determined.
Turkey inventory	: Not determined.
United States inventory (TSCA 8b)	: All components are listed or exempted.
Vietnam inventory	: Not determined.

The information stated in this section relates solely to the conformity of the chemical product with the countries Inventories. The information used to confirm the inventory status of this product may be based on additional data to the chemical composition shown in Section 3. Other regulations may apply for importation or marketing authorizations.

Section 16. Other information

History

Date of revision	: 2022/08/12
Date of previous revision	: No previous validation
Version	: 1

Key to abbreviations

: ATE = Acute Toxicity Estimate
: BCF = Bioconcentration Factor
: GHS = Globally Harmonized System of Classification and Labelling of Chemicals
: IATA = International Air Transport Association
: IBC = Intermediate Bulk Container
: IMDG = International Maritime Dangerous Goods
: LogPow = logarithm of the octanol/water partition coefficient
: MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)
: N/A = Not available
: SGG = Segregation Group
: UN = United Nations

Procedure used to derive the classification

Classification	Justification
Not classified.	

Additional details on the supplier of the product



TotalEnergies

SERIOLA QA 46

SDS # : 091290

SAUDI TOTAL PETROLEUM PRODUCTS CO. LTD 704, Zahran Business Center Sultan street - Tower A , 7th floor PO Box 4861, Jeddah 21463 K.S.A Tel: +966 12 22 56 300 Fax: +966 12 22 56 311	TotalEnergies Marketing (FIJI) Pte Ltd Rona Street, Walu Bay GPO Box 168 Suva - Fiji Islands Tel: +679 3313 933 Fax: +679 330 2279	TotalEnergies Marketing (Cambodia) Co., Ltd. ANINA Building 6th Floor, No 240, St. 271, B.P600, 12351 Phnom Penh, Cambodia Tel: +855 23 218 630 Fax: +855 23 217 662	TOTAL JORDAN Reem Center, 4th Floor 244 Arar Street, Wadi Saqra P.O. Box 831285, Amman 11183 Jordan Tel: +962 6 500 80 05 Fax: +962 6 500 80 08
TotalEnergies Marketing Lebanon SAL Rue Achrafieh, Imm. Tilal Bloc B, 2ème Etage B.P. 11-3636 Beyrouth - Liban Tel : + 961 1 21 22 50 Fax: + 961 1 21 21 33	TotalEnergies Marketing Middle East FZE Office 3901, 39th Floor, Uborra Commerical Tower, Business Bay, Al Abraj Street, PO Box 14871 Dubai, United Arab Emirates	TotalEnergies Marketing Asia-Pacific Middle East Pte Ltd McGregor Street Lot.19 Sec.8 Level 7, Deloitte Haus PO BOX 1784, Port Moresby, NCD Papua New Guinea Tel: +675 7999 6001	TotalEnergies Marketing India Private Limited 3rd Floor, The Leela Galleria, Andheri - Kurla Road, Andheri (East), Mumbai Maharashtra State, INDIA 400059 Tel: +91 22 6723 2500 Fax: +91 22 6723 2600
TotalEnergies Marketing Pacifique Immeuble Le Centre 30 route de la Baie des Dames, Imm. Le Centre, Ducos BP 717, 98845 Noumea Cedex Tel: +687 27 90 50 Fax: +687 27 29 90	TOTAL PARCO PAKISTAN LTD 10 Tariq Block, New Garden Town Lahore 54700, Pakistan Tel: +92 42 111 709 709 Fax: +92 42 354 683 66	TotalEnergies Marketing Polynésie Fare Ute Papette Postal address: B.P. 64, 98713 Papeete Tel: +689 40 48 50 50 Fax: +689 40 48 05 03	

References : Not available.

Indicates information that has changed from previously issued version.

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.